

## Антистатический шланг Layflat

Продукция	Диаметр/мм	Рабочее давление/МПа	Давление на разрыв/МПа	Вес/Кг/м	Прочность на растяжение/Кн
Ø50/1.0	51	1.0	3.0	0.55	
Ø50/1.6	51	1.6	4.8	0.65	
Ø50/3.5	51	3.5	10.5	0.90	
Ø65/1.0	63	1.0	3.0	0.65	
Ø65/1.6	63	1.6	4.8	0.95	
Ø80/0.8	76	0.8	2.4	0.75	
Ø80/1.0	76	1.0	3.0	0.80	
Ø80/1.6	76	1.6	4.8	1.25	
Ø100/1.0	102	1.0	3.0	1.20	80
Ø100/1.0(j)	102	1.0	3.0	1.40	100
Ø100/1.6	102	1.6	4.8	1.45	80
Ø125/1.0	127	1.0	3.0	1.60	120
Ø150/1.0	152	1.0	3.0	1.80	120
Ø150/1.6	152	1.6	4.8	2.50	150
Ø250/0.6	254	0.4	1.2	4.00	
Ø250/1.0	254	1.0	3.0		

## FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: